

MATERIAL SAFETY DATA SHEET

MANUFACTURER: Rendered by OEM manufacturer to:
iVekter Inc. for ezoBord
1550 Yorkton Court Unit 11
Buttrlington, Ontario Canada
L7P 5B7

EFFECTIVE DATE: March 25, 2008

EMERGENCY CONTACT: Phone: (416) 665-3571 ext 1
Fax: (416) 665-3571
Email: info@ezobord.com

I. PRODUCT IDENTIFICATION

PRODUCT NAME.....: 100% Polyester Thermalbonded Product
CHEMICAL FAMILY.....: Polyester Staple Fiber
CHEMICAL NAME.....: Finished Goods-Commodities.
MSDS NUMBER.....: MSDS 002

	<u>HMIS</u>
HEALTH	1
FLAMMABILITY	1
REACTIVITY	0

II. HAZARDOUS INGREDIENTS

None

III. PHYSICAL DATA

APPEARANCE.....: Solid
COLOR.....: Will vary with the addition of pigments
ODOR.....: Negligible
SOLUBILITY IN WATER.....: Insoluble
% VOLATILE BY VOLUME.....: Trace Amounts

IV. FIRE AND EXPLOSION DATA

FLASH POINT.....: Solid Material >200 degrees Fahrenheit
EXTINGUISHING MEDIA.....: Water, Foam, and Dry Chemical

IV. FIRE AND EXPLOSION DATA (continued)

SPECIAL FIRE FIGHTING PROCEDURES/UNUSUAL FIRE OR
EXPOLSION HAZARDS: Full emergency equipment with a self-contained
breathing apparatus and full protective clothing should be worn by all fire-
fighters. During a fire, irritating vapors and toxic gases may be generated.

V. HEALTH EFFECTS DATA

HUMAN EFFECTS OF
OVEREXPOSURE.....: No adverse health effects have been observed.
Human experience indicates no irritation upon skin
Contact with polyester fiber.

VI. FIRST AID

EYES.....: Irrigate immediately with water for at least 5 minutes.
Mechanical effects only.
SKIN.....: No adverse effects anticipated by this route of exposure
incidental to proper industrial handling.
INHALATION.....: Remove to fresh air.

VII. PERSONAL PROTECTION RECOMMENDATIONS

Safety glasses are advisable when cutting fiber. Adequate ventilation and
Respiratory protection is recommended when cutting fiber with a hot wire or
when flame laminating.

VIII. REACTIVITY DATA

STABILITY.....: Stable
POLYMERIZATION.....: Will not occur
INCOMPATIBILITY
(MATERIALS TO AVOID).....: None
HAZARDOUS DECOMPOSITION
PRODUCTS.....: Burning fiber may produce toxic
decomposition products including carbon monoxide, carbon dioxide,
acetaldehyde and other harmful products.

IX. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF MATERIAL IS RELEASED OR SPILLED:
Collect as normal combustible solid waste.

WASTE DISPOSAL METHOD: Conform to local, state and federal regulations.



X. TRANSPORTATION

DOT REGULATION: Not Regulated



XI. SPECIAL PRECAUTIONS AND STORAGE DATA

PRECAUTIONS TO BE TAKEN

IN HANDLING AND STORAGE: Store fiber in areas equipped with
sprinkler systems. FIBER WILL BURN! Do not expose fiber to open flames,
burning cigarettes, space heaters, naked lights, or other sources of intense heat.

If ignited, fiber will burn rapidly, consuming oxygen quickly and
producing toxic gases.



XII. ADDITIONAL INFORMATION

The information supplied herein is presented in good faith and believed to be
accurate to the best knowledge of iVekter Inc.. However, since
conditions of use are beyond our control, of iVekter Inc. makes no warranties,
expressed or implied, as to the use of this information or the fitness of this
product for a particular purpose.