



# ezoBord Specifications

## Colors

15 standard colors. Custom prints also available.

## Composition

100% Polyester (min 50% (+/-) recycled PET Fibre).

## Thickness

3/8" (9mm) standard. 1/2" (12mm) also available in limited colors.

## Weight

8.5lbs (+/- 5%) for 3/8" (9mm) sheet. 14.5lbs (+/- 5%) for 1/2" (12mm) sheet.

## Stiffness

70 (Shore Durometer).

## Dimensions

48' (1219mm) x 95 5/8' (2420mm) (+/- 1mm).

## Fire Testing

ASTM E-84 Class A / CAN ULC S102.

## Environment

Made with recycled polyester fibre. 50% +/- of which comes from recycled water bottles which contributes to LEED MR credit of Recycled content. No VOC's.

## Acoustics

Refer to ASTM C423 test data for specific 3/8" (9mm) absorption rates/frequency. ASTM C423/D: NRC = 0.75  
ASTM C423/A: NRC = 0.35 (subject to mounting conditions).

## Applications

Wall and ceiling, tackboards, visual and acoustical privacy barriers, acoustic canopies, and other custom applications.

## Product Variances

Variation in fiber mix and colour may occur. All products will be supplied within commercial tolerances.

## General

Tackable, impact resistant, bacteria resistant, moisture resistant, installation friendly.



[www.ezoBord.com](http://www.ezoBord.com)

ezoBord is a registered trademark of iVektor Inc.

## USA

Vervia Inc.  
325 Corporate Drive  
Elgin IL 60123

☎ 1-847-379-1822

✉ [sales@vervia.net](mailto:sales@vervia.net)

## CANADA

Arysonics Inc.  
825 Trillium Drive  
Kitchener ON N2R 1J9

☎ 1-844-441-1122

✉ [sales@arysonics.com](mailto:sales@arysonics.com)

## UNITED KINGDOM

ezoBord UK Ltd.  
3 Lloyd Rd Broadstairs.  
CT10 1HY, England

☎ +44 7981111236

✉ [sales\\_uk@ezobord.com](mailto:sales_uk@ezobord.com)